



## Sun Frost Super High Efficiency Electric Refrigerators

### Product List and Energy Usage

Model	Description	Daily Energy Use (amp hrs @ 12 VDC / kwh @ 110 VAC)		Dimensions (see clearances below)			Shipping (export add 40 lbs.)	
		at 70°F 21°C	at 90°F 32°C	Height	Width	Depth	Weight	Volume
<b>RF19*</b>	Half Refrigerator/Half Freezer	62 amp-hrs .77 kWh	82 amp-hrs 1.02 kWh	66"	34.5"	27.75"	320 lb.	46 C.F
<b>R19^</b>	Refrigerator Only	28 amp-hrs .33 kWh	47 amp-hrs .56 kWh	66"	34.5"	27.75"	310 lb.	46 C.F
<b>F19</b>	Freezer Only	100 amp-hrs 1.25 kWh	130 amp-hrs 1.63 kWh	66"	34.5"	27.75"	320 lb.	46 C.F
<b>RF16^</b>	Refrigerator-Freezer	40 amp-hrs .48 kWh	58 amp-hrs .70 kWh	62.5"	34.5"	27.75"	300 lb.	44 C.F
<b>RF12^</b>	Refrigerator-Freezer	24 amp-hrs .29 kWh	39 amp-hrs .47 kWh	49.5"	34.5"	27.75"	230 lb.	36 C.F
<b>R10</b>	Refrigerator Only	13 amp-hrs .17 kWh	23 amp-hrs .28 kWh	43.5"	34.5"	27.75"	215 lb.	32 C.F
<b>F10</b>	Freezer Only	55 amp-hrs .69 kWh	70 amp-hrs .88 kWh	43.5"	34.5"	27.75"	215 lb.	32 C.F
<b>RF4</b>	Refrigerator w/ ice tray	12 amp-hrs .14 kWh	18 amp-hrs .21 kWh	31.5"	34.5"	27.75"	160 lb.	23 C.F
<b>R4</b>	Refrigerator Only	8 amp-hrs .10 kWh	12 amp-hrs .14 kWh	31.5"	34.5"	27.75"	160 lb.	23 C.F
<b>F4</b>	Freezer Only	28 amp-hrs .35 kWh	36 amp-hrs .45 kWh	31.5"	34.5"	27.75"	160 lb.	23 C.F
<b>RFVB134a+</b>	Vaccine Storage Unit	14 amp-hrs .17 kWh	23 amp-hrs .28 kWh	31.5"	34.5"	27.75"	200 lb.	27 C.F

**Voltage:** All models are available in 12 volt DC, 24 volt DC, 110AC, or 220AC. Listed energy consumptions are for 12 volt units and 110AC; 24 volt units use half the listed amp hours. KWHs are listed for AC units.

**Colors:** A wide variety of custom laminates and wood veneers are available (see below). Standard laminate color is white. Follow these links for more info about laminates and veneers: [www.formica.com](http://www.formica.com) • [www.wilsonart.com](http://www.wilsonart.com) • [www.nevamar.com](http://www.nevamar.com)

**Clearance:** The doors are mounted on a continuous stainless steel piano-style hinge. **It is important to allow an additional 3.75" width on the hinge side for the door to open.** All units require minimum 6" clearance above the unit to allow for heat ventilation. Also, PLEASE NOTE: Oak veneers add a quarter of an inch to overall exterior dimensions, all other wood veneers add a half an inch.

\* Model RF19: Choice of Freezer on top or bottom.

^ Models R19, RF16 and RF12: ENERGY STAR® qualified models.

+ Model RFVB: Crated for export.

**Powerful Renewable Energy Solutions™**  
18388 Periwinkle Lane, Mount Vernon, WA. 98274  
360-422-5610  
[www.firemountainsolar.com](http://www.firemountainsolar.com)

## Interior Dimensions

Model	Freezer					Refrigerator					Total Volume	
	Dimensions (inches)			Volume		Dimensions (inches)			Volume		CF	Liters
	Height	Width	Depth	CF	Liters	Height	Width	Depth	CF	Liters	CF	Liters
<b>RF19</b>	24	28	20.75	8.07	228.5	24	28	20.75	8.07	228.5	16.1	457
<b>R19*</b>	24	28	20.75	8.07	228.5	24	28	20.75	8.07	228.5	16.1	457
<b>F19*</b>	24	28	20.75	8.07	228.5	24	28	20.75	8.07	228.5	16.1	457
<b>RF16+</b>	13	26	20	3.91	110.8	31	28	20.75	10.4	295.2	14.3	406
<b>RF12</b>	6.5	26	21	2.05	58.2	24	28	20.75	8.07	228.5	10.1	286.7
<b>R10</b>	NA	NA	NA	NA	NA	28	27.5	20.5	9.13	258.7	9.13	258.7
<b>F10</b>	28	27.5	20.5	9.13	258.7	NA	NA	NA	NA	NA	9.13	258.7
<b>RFVB</b>	4	26	20	1.2	34.1	6	26	20	1.8	51.1	3.0	85.2
<b>RF4</b>	2.25	26	20	.68	19.2	10.5	26	20	3.16	89.5	3.84	108.7
<b>R4</b>	NA	NA	NA	NA	NA	13	26	20	3.91	110.7	3.91	110.8
<b>F4</b>	13	26	20	3.91	110.8	NA	NA	NA	NA	NA	3.91	110.8

\* Unit has two equal size compartments – both refrigerator for R19, both freezer for F19.  
 + RF16 has the largest refrigerator compartment.

## Refrigerator and Freezer Crated Dimensions

Model	Height	Width	Depth	CF	CM
<b>19's</b>	72"	37"	30"	46	1.31
<b>16's</b>	69"	37"	30"	44	1.25
<b>12's</b>	56"	37"	30"	36	1.02
<b>10's</b>	50"	37"	30"	32	0.91
<b>4's</b>	36"	37"	30"	23	0.65
<b>RFVB*</b>	37"	39"	31"	27	0.76

\*Crated for Export