



RENEWABLE ENERGY PRODUCT LINE



MODEL	BCI	PLATES PER CELL	100 HR Rate	RESERVE CAP (RC)	CCA @ 0° F	MCA @ 32° F	LENGTH Inches / cm	WIDTH Inches / cm	HEIGHT Inches / cm	WET WEIGHT lbs / kg	DRY WEIGHT lbs / kg
Section A 2-Volt 1 Cell Polypropylene Container											
S-1380	EKG	43	1380	2283	2473	3091	13 3/8" 33.97 cm	7 1/8" 18.10 cm	17" 43.18 cm	115 lbs 52.16 kg	82 lbs 37.19 kg
S-1590	EKG	49	1596	2610	n/a	n/a	13 3/8" 33.97 cm	7 1/8" 18.10 cm	17" 43.18 cm	121 lbs 54.88 kg	86 lbs 39.01 kg
S-1725	EKG	53	1728	2828	n/a	n/a	13 3/8" 33.97 cm	7 1/8" 18.10 cm	17" 43.18 cm	125 lbs 56.70 kg	92 lbs 41.72 kg
Section B 6-Volt 3 Cell Polypropylene Container											
S-460	EKG	15	466	761	1066	1333	12 1/2" 31.75 cm	7 1/8" 18.10 cm	16 3/4" 42.55 cm	115 lbs 52.16 kg	82 lbs 37.19 kg
S-530	EKG	17	532	870	1218	1523	12 1/2" 31.75 cm	7 1/8" 18.10 cm	16 3/4" 42.55 cm	127 lbs 57.61 kg	92 lbs 41.72 kg
S-600	EKG	19	599	979	1370	1713	12 1/2" 31.75 cm	7 1/8" 18.10 cm	16 3/4" 42.55 cm	131 lbs 59.42 kg	103 lbs 46.72 kg
Section C 12-Volt 6 Cell Polypropylene Container											
24 HT 80	24	7	106	163	324	405	11" 27.50 cm	6 3/4" 16.88 cm	9 1/2" 23.75 cm	50 lbs 22.68 kg	38 lbs 17.24 kg
27 HT 90	27	9	120	183	405	506	12 1/2" 31.25 cm	6 3/4" 16.88 cm	9 1/2" 23.75 cm	62 lbs 28.12 kg	46 lbs 20.87 kg
T12 250	Spec	9	266	435	648	810	15 3/8" 38.44 cm	7" 17.50 cm	14 3/8" 35.94 cm	140 lbs 63.50 kg	97 lbs 44.00 kg
Section D 2-Volt 1 Cell Dual Container											
2 KS 33P	Spec	33	2490	4915	4952	6190	15 7/16" 38.59 cm	8 5/16" 21.10 cm	24 13/16" 63.02 cm	208 lbs 94.35 kg	145 lbs 65.78 kg
2 YS 31P	Spec	31	3426	7772	5740	7175	15 1/2" 38.75 cm	9" 22.90 cm	31 5/8" 79.06 cm	285 lbs 129.27 kg	200 lbs 90.72 kg
Section E 4-Volt 2 Cell Dual Container											
4 CS 17P	Spec	17	770	1083	1689	2111	14 3/8" 35.94 cm	8 1/4" 20.63 cm	18 1/4" 45.63 cm	128 lbs 58.06 kg	98 lbs 44.45 kg
4 KS 21P	Spec	21	1557	3575	3095	3869	15 3/4" 39.38 cm	9 3/8" 23.81 cm	24 3/4" 62.87 cm	267 lbs 121.11 kg	216 lbs 97.98 kg
4 KS 25P	Spec	25	1904	4290	3714	4643	15 3/4" 39.38 cm	10 5/8" 26.56 cm	24 3/4" 62.87 cm	315 lbs 142.88 kg	220 lbs 99.79 kg
All capacities based on specific gravities of 1.280. Reduce capacities 5% for 1.265 specific gravity and 10% for specific gravities of 1.250											

MODEL	BCI	PLATES PER CELL	100 HR Rate	RESERVE CAP (RC)	CCA @ 0° F	MCA @ 32° F	LENGTH Inches / cm	WIDTH Inches / cm	HEIGHT Inches / cm	WET WEIGHT lbs / kg	DRY WEIGHT lbs / kg
Section F 6-Volt 3 Cell Dual Container											
6 HHG 31P	Spec	31	458	696	1444	1805	20 3/4" 51.88 cm	8" 20.00 cm	11 7/8" 29.69 cm	125 lbs 56.70 kg	96 lbs 43.55 kg
6 EHG 31 P	Spec	31	545	830	1721	2151	20 3/4" 51.88 cm	8" 20.00 cm	12 3/4" 31.88 cm	133 lbs 60.33 kg	104 lbs 47.17 kg
6 CS 17P	Spec	17	770	1083	1357	1696	22" 55.00 cm	8 1/4" 20.63 cm	18 1/4" 45.63 cm	221 lbs 100.24 kg	178 lbs 80.74 kg
6 CS 21P	Spec	21	963	1353	1740	2175	22" 55.00 cm	9 3/4" 24.38 cm	18 1/4" 45.63 cm	271 lbs 122.92 kg	217 lbs 98.43 kg
6 CS 25P	Spec	25	1156	1624	2088	2610	22" 55.00 cm	11 1/4" 28.13 cm	18 1/4" 45.63 cm	318 lbs 144.24 kg	254 lbs 115.21 kg
Section G 8-Volt 4 Cell Dual Container											
8 HHG 31 P	8 Volt	31	458	696	1445	1806	27" 67.50 cm	8" 20.00 cm	11 7/8" 29.69 cm	167 lbs 75.75 kg	128 lbs 58.06 kg
8 EHG 31 P	8 Volt	31	545	830	1721	2151	27" 67.50 cm	8" 20.00 cm	12 3/4" 31.88 cm	178 lbs 80.74 kg	139 lbs 63.05 kg
8 CS 17P	8 Volt	17	770	1083	1351	1696	28 1/4" 70.63 cm	8 1/4" 20.63 cm	18 1/4" 45.63 cm	294 lbs 133.36 kg	238 lbs 107.95 kg
8 CS 25P	8 Volt	25	1156	1624	2027	2534	28 1/4" 70.63 cm	11 1/4" 28.13 cm	18 1/4" 45.63 cm	424 lbs 192.32 kg	342 lbs 155.12 kg
Section H 12-Volt 6 Cell Dual Container											
12 CS 11P	Spec	11	503	677	845	1056	22" 55.00 cm	11 1/4" 28.13 cm	18 1/4" 45.63 cm	272 lbs 123.38 kg	220 lbs 99.79 kg
All capacities based on specific gravities of 1.280. Reduce capacities 5% for 1.265 specific gravity and 10% for specific gravities of 1.250											



RENEWABLE ENERGY PRODUCT WARRANTY



We build one mean battery and we back them with comprehensive warranties that lead the industry in length of coverage. We're confident that our batteries will perform time after time, year after year. However, should a problem arise, you can be confident that you're covered better than any other battery warranty in the business.

Surrette Battery, herein referred to as the Company, warrants that batteries sold by it are merchantable and free of defects in workmanship and material at the time they are shipped from the Company's factory.

In the event that the Company makes a drop shipment to a distributor's customer, that customer must be instructed to perform an inspection of the goods BEFORE signing the delivery slip. The Company is not responsible for damaged product reported after shipment has been signed "Received in Good Condition".

ALL SHIPMENTS SHOULD BE THOROUGHLY INSPECTED FOR DAMAGE BEFORE SIGNING THE DELIVERY SLIP.

The Company will replace or, at its option, repair any Rolls Renewable Energy battery sold by it that fails to conform to the warranty stated below on a NO CHARGE BASIS as follows:

The Company makes no warranty with respect to its batteries other than the warranty stated below. All implied warranties of merchantability and all expressed and implied warranties of any other kind are hereby excluded.

SERIES 4000

Failure within 24 months from the date placed in service yields FREE REPLACEMENT, not including freight charges from the factory to the applicable destination. After the first 24 months of service, defective batteries will be adjusted for a period of up to 84 months prorated from the date first in service at prices in effect at time of adjustment.

SERIES 5000

Failure within 36 months from the date placed in service yields FREE REPLACEMENT, not including freight charges from the factory to the applicable destination. After the first 36 months of service, defective batteries will be adjusted for a period of up to 120 months prorated from the date first in service at prices in effect at time of adjustment.

To claim a manufacturing warranty, proof of purchase must be presented, showing the date of purchase and the battery's serial number. The battery must be tested by an Authorized Battery Outlet for actual defect, and upon confirmation of the defect, the warranty will be administered.

The Warranty does not cover shipping damage, cracked covers, cracked cases, bulged cases from heat, freezing or explosion, discharged batteries, the use of undersized batteries damaged from electrical equipment. This warranty covers only manufacturing defects.